

806AA
 FLEXOR 6
 SAE 100 R6 - EN 854 R6



Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : ONE HIGH TENSILE TEXTILE BRAID
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : LOW PRESSURE HIDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER. SPECIALLY DESIGNED FOR USE IN "PUSH ON" APPLICATIONS
 Constant operation : -40°C +100°C (T max air = +70°C)
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random
 Branding : ALFAGOMMA FLEXOR 6 ID... - WP ... MPa (... PSI) - SAE 100R6-EN854 R6 -DN ... - Q/yr
 Note : * Alfagomma proprietary hose Not listed in SAE J517 100 R6 spec.

S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>806AA006008JA8</u>	6	1/4	-4	12,7	0,5	2,8	400	11	1600	64	2,6	0,13	9
<u>806AA008008JA8</u>	8	5/16	-5	14,3	0,56	2,8	400	11	1600	76	3	0,13	9
<u>806AA010008JA8</u>	10	3/8	-6	15,9	0,63	2,8	400	11	1600	76	3	0,17	11
<u>806AA012008JA8</u>	13	1/2	-8	19,8	0,78	2,8	400	11	1600	102	4,1	0,23	15
<u>806AA016008JA8</u>	16	5/8	-10	23	0,91	2,4	350	10	1400	107	4,3	0,27	18
<u>806AA020008JA8</u>	19	3/4	-12	26,9	1,06	2,1	300	8	1200	152	6,1	0,37	25
<u>806AA025008JA8*</u>	25	1	-16	33,4	1,31	1,7	250	7	1000	203	8,1	0,49	33