

8B7AA
 FLEXORBLAST 25K
 ALFAGOMMA PROPRIETARY HOSE



- Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : FOUR HIGH TENSILE STEEL SPIRALS (4S)
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : VERY HIGH PRESSURE WATER JETTING
 Constant operation : -40°C +93°C
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random
 Branding : ALFAGOMMA FLEXORBLAST 25K ID ... WP ... MPa - ... PSI WATERBLAST USE ONLY MADE IN ITALY - Q/yr
 Note : S.F.: 2,5:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>8B7AA020002WA8</u>	19	3/4	-12	32,2	1,27	70	10000	175	25000	280	11,2	1,62	109
<u>8B7AA025002WA8</u>	25	1	-16	38,7	1,52	70	10000	175	25000	320	12,8	1,99	133