

8T8AA
 FLEXOR 2SN - R2AT HF
 EN 853 2SN - SAE 100 R2AT



Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : TWO HIGH TENSILE STEEL BRAIDS (2B)
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
 Constant operation : -40°C +100°C (T max air = +70°C)
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random up to 1" - 40 mt. max over 1"
 Branding : ALFAGOMMA FLEXOR 2AT/2SN ID... - WP ... MPa (... PSI) - SAE 100 R2AT - EN 853 2SN - DN ... - Q/yr
 Note : MSHA cover available: Code 846AA

S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>8T8AA00500ISB8</u>	5	3/16	-3	13,1	0,52	42	6000	168	24000	90	3,6	0,29	19
<u>8T8AA00600ISB8</u>	6	1/4	-4	14,6	0,57	40	5800	160	23200	100	4	0,36	24
<u>8T8AA00800ISB8</u>	8	5/16	-5	16,2	0,64	35	5000	140	20000	115	4,6	0,42	28
<u>8T8AA01000ISB8</u>	10	3/8	-6	18,5	0,73	33	4800	132	19200	125	5	0,51	34
<u>8T8AA01200ISB8</u>	13	1/2	-8	21,5	0,85	27,5	4000	110	16000	175	7	0,64	43
<u>8T8AA01600ISB8</u>	16	5/8	-10	24,7	0,97	25	3630	100	14520	200	8	0,74	50
<u>8T8AA02000ISB8</u>	19	3/4	-12	29	1,14	21,5	3120	86	12480	240	9,6	0,91	61
<u>8T8AA02500ISB8</u>	25	1	-16	36,9	1,45	16,5	2400	66	9600	300	12	1,32	88
<u>8T8AA032482MB8</u>	32	1.1/4	-20	46,5	1,83	12,5	1820	50	7280	420	16,8	1,93	129
<u>8T8AA038552MB8</u>	38	1.1/2	-24	53,7	2,11	9	1310	36	5240	500	20	2,41	161
<u>8T8AA051672MB8</u>	51	2	-32	66,5	2,62	8	1160	32	4640	630	25,2	2,96	198