

T-130 AK  
COMPRESSED AIR 40 BAR (600 PSI) - STEEL REINFORCED



TUBE : BLACK SBR/NBR - OIL MIST RESISTANT

REINFORCEMENT : HIGH TENSILE STEEL CORDS

COVER : YELLOW SBR - ABRASION AND OZONE RESISTANT - PIN PRICKED

APPLICATION : HIGH PRESSURE COMPRESSED AIR DESIGNED FOR HEAVY DUTY MINE AND QUARRY APPLICATIONS WHERE LONG SERVICE LIFE AND MAXIMUM SAFETY IS REQUIRED.

SAFETY FACTOR : 4:1

TEMPERATURE : -30°C +80°C (-22°F +176°F)

BRAND TEXT : ALFAGOMMA -ITALY- T-130 STEEL AIR

BRAND TYPE : EMBOSSED

APPROVALS :

NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<a href="#"><u>130AK019311X03</u></a>	19	3/4	31	6	810	40	600		95	30,5	30,5
<a href="#"><u>130AK025371X03</u></a>	25	1"	37	6	1010	40	600		125	30,5	30,5
<a href="#"><u>130AK032441X03</u></a>	32	1" 1/4	44	6	1240	40	600		160	30,5	
<a href="#"><u>130AK038521X03</u></a>	38	1" 1/2	52	7	1660	40	600		190	15,25 / 30,5	30,5
<a href="#"><u>130AK051651X03</u></a>	51	2"	65	7	2350	40	600		255	15,25 / 30,5	30,5
<a href="#"><u>130AK063831X03</u></a>	63	2" 1/2	83	10	3570	30	450		315	15,25 / 30,5	30,5
<a href="#"><u>130AK076961X03</u></a>	76	3"	96	10	4260	30	450		380	30,5	30,5
<a href="#"><u>130AK102221X03</u></a>	102	4"	122	10	6150	30	450		510	15,25 / 30,5	30,5