

T-202 AA
GENERAL PURPOSE S&D 10 BAR (150 PSI) - EPDM



TUBE : BLACK EPDM
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
 COVER : BLACK EPDM - ABRASION AND OZONE RESISTANT
 APPLICATION : WATER SUCTION AND DELIVERY. ALSO SUITABLE FOR MILD CHEMICALS AND FERTILIZERS IN GENERAL INDUSTRIAL AND AGRICULTURAL APPLICATIONS. REFER TO CHEMICAL RESISTANCE CHART.
 SAFETY FACTOR : <= 127mm 3:1 >=152mm 2.5:1
 TEMPERATURE : -30°C +80°C (-22°F +176°F)
 BRAND TEXT : ALFAGOMMA -ITALY- T-202 10 BAR (150 PSI) GENERAL PURPOSE - EPDM
 BRAND TYPE : GREEN LETTERS

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
202AA025352OB0	25	1"	35	5	700	10	150	100	100	20 / 30,5 / 61	61
202AA030402OB0	30	1 3/16	40	5	780	10	150	100	120	61	
202AA032422OB0	32	1" 1/4	42	5	820	10	150	100	128	30,5 / 61	61
202AA038482OB0	38	1" 1/2	48	5	960	10	150	100	152	30,5 / 61	61
202AA040502OB0	40	1" 9/16	50	5	1000	10	150	100	160	61	61
202AA045552OB0	45	1 3/4	55	5	1110	10	150	100	180	61	61
202AA051612OB0	51	2"	61	5	1240	10	150	100	204	20 / 30,5 / 61	61
202AA060722OB0	60	2" 3/8	72	6	1710	10	150	100	240	20	20
202AA063752OB0	63	2" 1/2	75	6	1780	10	150	90	252	20 / 30,5 / 61	30,5
202AA070822OB0	70	2 3/4	82	6	1990	10	150	90	280	20	20
202AA076882OB0	76	3"	88	6	2140	10	150	90	304	20 / 30,5 / 61	30,5
202AA080922OB0	80	3" 1/8	92	6	2310	10	150	90	320	20	20
202AA090022OB0	90	3" 1/2	102	6	2700	10	150	90	360	30,5	30,5
202AA102142OB0	102	4"	114	6	3010	10	150	90	408	20 / 30,5 / 61	30,5
202AA110222OB0	110	4 5/16	122	6	3220	10	150	80	440	30,5	
202AA115272OB0	115	4 1/2	127	6	3340	10	150	80	460	30,5	
202AA120342OB0	120	4 3/4	134	7	4510	10	150	80	600	30,5	
202AA127412OB0	127	5"	141	7	4740	10	150	80	635	6,1 / 15,25 / 20 / 30,5	20
202AA152662OB0	152	6"	166	7	5970	10	150	80	760	6,1 / 7,625 / 15,25 / 20 / 30,5	20
202AA203212OB0	203	8"	221	9	9830	10	150	70	1015	6,1 / 7,625 / 10	
202AA254722OB0	254	10"	272	9	13450	10	150	60	1270	6,1	
202AA300222OB0	300	11 13/16	322	11	18390	10	150	60	1500	6,1	