

T-330 AH
**SATURATED STEAM 17 BAR (250 PSI) - STEEL REINFORCED
NFT 47263/13 BS 5342/2A DIN 2825**

TUBE : BLACK EPDM

REINFORCEMENT : HIGH TENSILE STEEL CORDS

COVER : RED EPDM - HEAT, ABRASION AND OZONE RESISTANT - PIN PRICKED

APPLICATION : SATURATED STEAM.

SAFETY FACTOR : 10:1

TEMPERATURE : -40°C +210°C (-40°F +410°F)

BRAND TEXT : ALFAGOMMA -ITALY- T-330 17 BAR (250 PSI) STEAM - DRAIN AFTER USE- BS 5342/A/2-NFT47263 CI T3
DIN2825 q/yy

BRAND TYPE : EMBOSSED

APPROVALS :
NOTE : DIAM. 63mm AND 76mm NOT COVERED BY ABOVE MENTIONED NORMS

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>330AH013253YA3</u>	13	1/2	25	6	560	17	250		130	15,25 / 30,5 / 61	61
<u>330AH016283YA3</u>	16	5/8	28	6	620	17	250		160	61	61
<u>330AH019323YA3</u>	19	3/4	32	6,5	730	17	250		190	15,25 / 30,5 / 61	61
<u>330AH019333YA3</u>	19	3/4	33	7	850	17	250		190	61	
<u>330AH025383YA3</u>	25	1"	38	6,5	900	17	250		250	15,25 / 30,5 / 61	61
<u>330AH025403YA3</u>	25	1"	40	7,5	1040	17	250		250	61	
<u>330AH032463YA3</u>	32	1" 1/4	46	7	1320	17	250		320	61	61
<u>330AH032483YA3</u>	32	1" 1/4	48	8	1500	17	250		320	61	
<u>330AH038523YA3</u>	38	1" 1/2	52	7	1540	17	250		380	61	61
<u>330AH038543YA3</u>	38	1" 1/2	54	8	1740	17	250		380	61	
<u>330AH051673YA3</u>	51	2"	67	8	2150	17	250		510	61	61
<u>330AH051693YA3</u>	51	2"	69	9	2400	17	250		510	61	
<u>330AH063833YA3</u>	63	2" 1/2	83	10	3720	17	250		630	30,5	30,5
<u>330AH076963YA3</u>	76	3"	96	10	4410	17	250		760	30,5	30,5