

T-505 OG
ACID-CHEMICAL S&D 16 BAR (240 PSI) - XLPE



TUBE : TRANSPARENT XLPE (CROSS LINKED POLYETHYLENE)
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
 COVER : GREEN EPDM - ABRASION AND OZONE RESISTANT
 APPLICATION : ACID AND CHEMICAL SUCTION AND DELIVERY. SUITABLE FOR 90% OF EXISTING CHEMICALS. REFER TO CHEMICAL RESISTANCE CHART.
 SAFETY FACTOR : 3:1
 TEMPERATURE : -20°C +65°C (-4°F +150°F)
 BRAND TEXT : ALFAGOMMA -ITALY- T-505 16 BAR (240 PSI) XLPE CHEMICAL - S&D
 BRAND TYPE : ORANGE LETTERS
 APPROVALS :
 NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>505OG019315AB0</u>	19	3/4	31	6	690	16	240	90	188	30,5	30,5
<u>505OG025375AB0</u>	25	1"	37	6	850	16	240	90	225	30,5	30,5
<u>505OG032445AB0</u>	32	1" 1/4	44	6	1010	16	240	90	263	30,5	30,5
<u>505OG038515AB0</u>	38	1" 1/2	51	6,5	1160	16	240	90	338	30,5	30,5
<u>505OG063795AB0</u>	63	2" 1/2	79	8	2320	16	240	90	450	30,5	
<u>505OG076925AB0</u>	76	3"	92	8	2780	16	240	80	525	30,5	30,5
<u>505OG102185AB0</u>	102	4"	118	8	3780	16	240	80	675	30,5	