

T-609 AA
 FUEL-OIL S&D 16 BAR (240 PSI)
 EXCEEDS EN 1761 TRbF 131/2



TUBE : BLACK CONDUCTIVE NBR
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
 COVER : BLACK CONDUCTIVE CR - ABRASION, OZONE, HYDROCARBON AND FIRE RESISTANT
 APPLICATION : FUEL AND OIL SUCTION AND DELIVERY. DESIGNED FOR LONG LASTING SERVICE IN HEAVY DUTY APPLICATIONS.
 SAFETY FACTOR : 3:1
 TEMPERATURE : -30°C +70°C (-22°F +158°F)
 BRAND TEXT : ALFAGOMMA -ITALY- T-609 16 BAR (240 PSI) PETROLEUM S&D - EN 1761:1999 - TRBF 131/2 - (omega) dia mm Q/YY"
 BRAND TYPE : YELLOW TRANSFER
 APPROVALS :

NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>609AA025376IEO</u>	25	1"	37	6	860	16	240	100	150	61	
<u>609AA032446IEO</u>	32	1" 1/4	44	6	1030	16	240	100	175	61	
<u>609AA038516IEO</u>	38	1" 1/2	51	6,5	1180	16	240	100	225	61	61
<u>609AA051676IEO</u>	51	2"	67	8	1820	16	240	100	275	30,5	
<u>609AA063796IEO</u>	63	2" 1/2	79	8	2380	16	240	90	300	30,5	
<u>609AA076926IEO</u>	76	3"	92	8	2860	16	240	90	350	30,5	30,5
<u>609AA102186IEO</u>	102	4"	118	8	3900	16	240	90	450	30,5	30,5
<u>609AA152726IEO</u>	152	6"	172	10	8310	16	240	80	760	30,5	