

# PVC Coated Polyester Fabric Ducting Hose



A) Steel helix embedded between the layers



B) Flame retardant PVC coated polyester fabric

**Colour:** grey

**Temperature range:** - 20°C +100°C (peaks +120°C)

**Features:** flexible duct made of flame resistant PVC Coated Polyester Fabric and reinforced by steel helix welded between the two layers. Axial compressibility: 8:1

**Flame retardant V(TM)-0 according to UL 94 and M2 grade according to NFP 92 503.**

**Applications:** Civil and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders & gas

## TECHNICAL DATA

Part Number	Inside Ø	Weigth	Bending radius	Roll length	Volume
	mm	g/n	mm	m	m <sup>3</sup>
TR 01 040.0 000.0	40	110	20	10	0,002
TR 01 051.0 000.0	51	135	26	10	0,003
TR 01 060.0 000.0	60	160	30	10	0,004
TR 01 063.0 000.0	63	170	32	10	0,005
TR 01 070.0 000.0	70	185	35	10	0,006
TR 01 076.0 000.0	76	200	38	10	0,006
TR 01 080.0 000.0	80	210	40	10	0,007
TR 01 090.0 000.0	90	240	45	10	0,009
TR 01 102.0 000.0	102	280	51	10	0,011
TR 01 110.0 000.0	110	300	55	10	0,013
TR 01 115.0 000.0	115	315	58	10	0,014
TR 01 120.0 000.0	120	325	60	10	0,016
TR 01 127.0 000.0	127	345	64	10	0,017

TR 01 130.0 000.0	130	355	65	10	0,018
TR 01 140.0 000.0	140	380	70	10	0,021
TR 01 152.0 000.0	152	410	76	10	0,025
TR 01 160.0 000.0	160	425	80	10	0,028
TR 01 180.0 000.0	180	475	90	10	0,035
TR 01 203.0 000.0	203	535	102	10	0,044
TR 01 228.0 000.0	228	600	114	10	0,055
TR 01 254.0 000.0	254	845	127	10	0,068
TR 01 279.0 000.0	279	925	140	10	0,082
TR 01 305.0 000.0	305	1010	153	10	0,098
TR 01 315.0 000.0	315	1045	158	10	0,104
TR 01 330.0 000.0	330	1090	165	10	0,114
TR 01 356.0 000.0	356	1180	178	10	0,132
TR 01 406.0 000.0	406	1340	203	10	0,171

**Systech Industries Sdn Bhd**

No. 9, Jalan LP 8/6, Taman Lestari Perdana, 43300 Seri Kembangan, Selangor, Malaysia.

Tel +603 8948 1808 Fax +603 8948 8808 Website: [www.systech-ind.com](http://www.systech-ind.com)